


等辺アングル



製作区分	型番	形状寸法 (mm)						断面積 (mm ²)	単位質量 (kg / m)	材質区分				
		A	T	R 1	R 2	R 3	R 4			I	II	III	IV	
角・平角	A	S 94220 A	100	4	-	-	-	-	784	2.117		○		
	N	S 94108	40	3	3	1.5	-	-	232	0.626		○		
等辺アングル	N	S 94218	50	4	6.5	3	-	-	389	1.035			○	○
	N	S 94305	50	5	5	2.5	-	-	478	1.291		○	○	○
	N	S 94412	50	6	6	3	-	-	568	1.534		○	○	○
不等辺アングル	N	S 94601	50	8	8	4	-	-	743	2.006		○	○	○
	N	S 94322	60	5	-	-	-	-	575	1.553		○	○	○
	N	S 94401	60	6	6	3	-	-	688	1.858		○	○	○
	N	S 94406	65	6	6	3	-	-	748	2.02		○	○	○
チャンネル	N	S 94605	65	8	6	3	-	-	980	2.646		○	○	○
	N	S 94407	70	6	6	3	-	-	808	2.182		○	○	○
	N	S 94603	70	8	8	4	-	-	1063	2.87		○	○	○
	N	S 94413	75	6	6	4	-	-	865	2.336		○	○	○
I・H型	N	S 94702	75	9	9	4.5	-	-	1278	3.451	○	○	○	○
	N	V 70002	75	10	5	5	-	-	1395	3.765		○		
等辺角管	N	S 94803	75	10	-	-	-	-	1400	3.78		○	○	○
	N	V 70001	76.2	4.78	6.35	4.78	0.25	0.25	705	1.904			○	○
	N	S 94707	80	9	9	4.5	-	-	1368	3.694		○	○	○
	N	S 94704	90	9	9	4.5	-	-	1548	4.18		○	○	○
不等辺角管	N	S 94408	100	6	10	5	-	-	1175	3.173		○	○	○
	N	S 94805	100	10	10	5	-	-	1911	5.16		○	○	○
	N	S 94809	130	12	12	8.5	-	-	2976	8.035		○	○	○
S形材	N	V 90002	150	6	3	1	1	1	1765	4.766		○	○	○
	K	S 94806	150	15	15	7.5	-	-	4299	11.607		○	○	○
	S	E0002	60	6	8.5	4	-	-	692.6	1.87			○	
	S	E0003	25	5	-	-	-	-	225.0	0.608			○	
	S	E0006	75	9	8.5	4	-	-	1277.7	3.45			○	
丁形材	S	E0009	75	9	-	-	-	-	1269.0	3.426			○	
	S	E0013	12	1.2	-	0.3	0.3	0.3	27.3	0.074			○	
	S	E0017	15	1	-	-	-	-	29.0	0.078			○	
パイプ	S	30012	50	4	4	2	-	-	386	1.041			○	
	S	30044	20	1.5	-	-	-	-	58	0.157			○	
	S	30045	25	2	-	-	-	-	96.0	0.259			○	
	S	30046	30	2	-	-	-	-	116.0	0.313			○	
	S	30054	20	3	-	-	-	-	111.0	0.3			○	
	S	30056	40	4	-	-	-	-	304.0	0.821			○	
	S	30074	30	1.5	-	-	-	-	87.8	0.237			○	
	S	30083	30	5	-	-	-	-	275.0	0.743			○	
	S	30086	15	2	-	-	-	-	56.0	0.151			○	
	S	30089	30	3	-	-	-	-	171.0	0.462			○	

製作区分	型番	形状寸法 (mm)						断面積 (mm ²)	単位質量 (kg / m)	材質区分			
		A	T	R 1	R 2	R 3	R 4			I	II	III	IV
S	30094	30	3	-	-	-	-	171.0	0.462			○	
S	30129	50	6	6	3	-	-	568.0	1.505			○	
S	30134	65	8	8	4.5	-	-	981.1	2.649			○	
S	30152	50	3	-	-	-	-	291.0	0.786			○	
S	30223	20	2	-	-	-	-	76.0	0.205			○	
S	30225	25	3	-	-	-	-	141.0	0.381			○	
S	30228	40	3	-	-	-	-	231.0	0.624			○	
S	30230	50	4	-	-	-	-	384.0	1.037			○	
S	30231	50	5	-	-	-	-	475.0	1.283			○	
S	30232	50	6	6.5	4.5	-	-	564.4	1.524			○	
S	30236	75	6	6	3	-	-	86.8	2.343			○	
S	30238	15	1.5	-	-	-	-	42.8	0.115			○	
S	30294	35	3	-	-	-	-	201.0	0.543			○	
S	30295	40	5	-	-	-	-	375.0	1.013			○	
S	30296	60	5	-	-	-	-	575.0	1.553			○	
S	30297	15	3	-	-	-	-	81.0	0.219			○	
S	30298	40	2	-	-	-	-	156.0	0.421			○	
S	30302	100	10	8.5	4	-	-	1908.7	5.153			○	
S	30305	25	1.5	-	0.3	0.3	0.3	72.7	0.196			○	
S	30315	10	2	-	-	-	-	36.0	0.097			○	
S	30316	35	4	-	-	-	-	264.0	0.713			○	
S	30319	40	6	-	-	-	-	444.0	1.199			○	
S	30320	80	8	8.5	4	-	-	1224.7	3.306			○	
S	30323	80	8	-	-	-	-	1216.0	3.283			○	

角・平角

等辺アングル

不等辺アングル

チャンネル

I・H型

等辺角管

不等辺角管

S形材

T形材

パイプ

六角