


不等辺アングル



製作 区分	型 番	形 状 寸 法 (mm)							断 面 積 (mm ²)	単位質量 (kg / m)	材 質 区 分			
		A	B	T	R 1	R 2	R 3	R 4			I	II	III	IV
A	SA 0012	20	20	2	—	—	—	—	76	0.205		○		
A	W 57013	50	45	6	1	0.5	0.5	0.5	533.9	1.442		○		
A	W 77003	75	50	8	8	4	1	1	942.2	2.544		○		
N	S 95147	25	20	3	3	—	—	—	128	0.346			○	
N	S 95221	40	20	4	4	—	—	—	227	0.604		○	○	
N	S 95211	40	30	4	4	2	0.5	0.5	266	0.718			○	
N	W 40002	45	30	5	5	0.5	0.5	0.5	355.1	0.959				
N	S 95225	45	35	4.5	3	—	—	—	342	0.91			○	
N	S 95204	50	35	4	4	2	—	—	326	0.88		○	○	
N	S 95222	50	35	4	6.5	3	—	—	329	0.875			○	
N	S 95329	60	35	5	6.5	3	—	—	455	1.229		○	○	
N	S 95226	60	40	4	4	2	—	—	386	1.027			○	
N	S 95333	60	40	5	5	—	—	—	480	1.296		○	○	
N	S 95404	60	40	6	6	3	—	—	568	1.534		○	○	
N	W 60002	65	40	4	4	—	—	—	407.4	1.1		○		
N	S 95304	65	50	5	5	2.5	—	—	553	1.493		○	○	
N	S 95406	70	55	6	3	2	—	—	714	1.928		○	○	
N	S 95302	75	50	5	6.5	3	—	—	605	1.634		○	○	
N	S 95330	80	42.5	5	5	—	—	—	593	1.601		○	○	
N	S 95305	85	50	5	5	2.5	—	—	653	1.763		○	○	
N	S 95331	100	40	5	5	—	—	—	680	1.836		○	○	
N	S 95146	100	50	3	0.5	—	—	—	441	1.195		○		
N	S 95326	100	50	5	6	3.5	0.5	0.5	727	1.963		○	○	
N	S 95506	100	65	7	10	5	—	—	1117	3.016		○	○	
N	S 95332	100	70	5	5	—	—	—	830	2.241		○	○	
N	S 95414	100	75	6	6	3	—	—	1018	2.749		○	○	
N	S 95801	100	75	10	10	5	—	—	1661	4.485		○	○	
N	S 95502	125	75	7	7	3.5	—	—	1356	3.661		○	○	
N	S 95803	125	75	13	10	7	—	—	2431	6.564		○	○	
N	S 95805	125	90	13	13	6.5	—	—	2644	7.139		○	○	
N	S 95701	150	75	9	12	8.5	—	—	1944	5.249		○	○	
N	S 95328	165	53	5	—	—	—	—	1065	2.876		○	○	
N	S 95818	195	40	10	8	—	—	—	2264	6.113		○	○	
S	E 1004	50	35	4	—	—	—	—	324.0	0.875		○		
S	E 1015	70	20	4	—	0.3	0.3	0.3	343.9	0.929		○		
S	E 1017	50	25	3	—	0.3	0.3	0.3	215.9	0.583		○		
S	E 1018	20	9	1.6	—	0.3	0.3	0.3	43.7	0.118		○		
S	E 1019	75	50	5	—	0.3	0.3	0.3	599.9	1.62		○		
S	E 1020	30	20	3	—	0.3	0.3	0.3	140.9	0.38		○		
S	E 1024	70	50	4	—	0.3	0.3	0.3	463.9	1.253		○		

角・平角	製作 区分	型 番	形 状 寸 法 (mm)						断 面 積 (mm ²)	単位質量 (kg／m)	材 質 区 分				
			A	B	T	R 1	R 2	R 3			R 4	I	Ⅱ	Ⅲ	Ⅳ
等辺アングル	S	E 1026	15	10	2	－	－	－	－	46.0	0.124		○		
	S	E 1028	30	10	1.5	－	－	－	－	57.8	0.156		○		
	S	31080	20	15	2	－	－	－	－	66.0	0.178		○		
	S	31096	20	15	1.5	－	－	－	－	50.0	0.136		○		
不等辺アングル	S	31204	25	20	4	4	2	－	－	165.7	0.447		○		
	S	31260	25	19	3	1	1.5	－	－	123.0	0.33		○		
	S	31312	40	20	2	－	－	－	－	116.0	0.313		○		
	S	31313	40	20	3	－	－	－	－	171.0	0.462		○		
チャンネル	S	31314	34	29	4	1	4	－	1	229.0	0.619		○		
	S	31332	20	10	1.5	－	－	－	－	43.0	0.115		○		
	S	31365	70	60	3	2	0.5	0.5	－	382.0	1.03		○		
	S	31374	25	15	1.5	－	－	－	－	58.0	0.156		○		
I・H型	S	31391	15	10	1.5	－	－	－	－	35.3	0.095		○		
	S	31400	30	20	2	－	－	－	－	96.0	0.259		○		
	S	31422	30	15	2	－	－	－	－	86.0	0.232		○		
	S	31440	65	35	2	2	1	1	4	192.6	0.52		○		
等辺角管	S	31450	75	50	5	5	2.5	－	－	602.7	1.627		○		
	S	31470	25	20	2	－	－	－	－	86.0	0.232		○		
	S	31471	50	35	4	－	－	－	－	324.0	0.875		○		
	S	31472	60	40	5	－	－	－	－	475.0	1.283		○		
不等辺角管	S	31473	50	25	2	－	－	－	－	146.0	0.394		○		
	S	31477	150	100	5	－	－	－	－	1224.9	3.307		○		
S形材															
T形材															
パイプ															
六角															